



Anti-glare & High quality light, the professional choice for replacing metal halide lamps or halogen lamps. Compact spotlight with passive cooling that is able to impress--thanks to its efficiency, good glare control, excellent colour rendering and perfect light output.



专业光学设计，高品质光输出，完美替代传统卤素灯和金卤灯。独特的空气对流散热技术提高光的输出效率，无眩光，光线自然、柔和均匀，高显指、高照度，完美呈现被照物色泽。

# The professional choice for replacing Metal Halide

专业商业照明、完美光色

- The professional choice for replacing Metal Halide
- Three wired track light
- Extruded aluminium spotlight housing
- Simple and elegant appearance
- No flicker
- Anti-glare reflector design, UGR<15
- Lock design for reflector, easy replacement of reflector for angles
- Convective cooling design, improved heat dissipation
- Spotlight head rotates through 350°, pivots through 90°
- Service life up to 50,000 hours at 70 % luminous flux



TL21

TL22

TL23

- 专业商业照明，替换传统金卤灯
- 三线轨道设计
- 本体铝挤型材高效散热
- 简洁大方外观工业设计
- 无频闪驱动
- 防眩光铝反光杯，UGR<15
- 反光杯扣装结构，方便角度更换
- 对流冷却设计，优化散热
- 灯体350° 旋转，90° 摆头调节，全方位照射
- 使用寿命长达50,000小时

TL21




TL22



TL23




Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号	
12W	90	▲ 18°	800lm	3000K	White	TL21-12W-930-18-W	
			750lm	3000K	Black	TL21-12W-930-18-B	
		▲ 28°	800lm	4000K	White	TL21-12W-940-18-W	
			750lm	4000K	Black	TL21-12W-940-18-B	
		▲ 36°	800lm	3000K	White	TL21-12W-930-28-W	
			750lm	3000K	Black	TL21-12W-930-28-B	
	800lm		4000K	White	TL21-12W-940-28-W		
	750lm		4000K	Black	TL21-12W-940-28-B		
	12W	90	▲ 18°	800lm	3000K	White	TL21-12W-930-36-W
				750lm	3000K	Black	TL21-12W-930-36-B
			▲ 28°	800lm	4000K	White	TL21-12W-940-36-W
				750lm	4000K	Black	TL21-12W-940-36-B
▲ 36°			800lm	3000K	White	TL21-12W-930-36-W	
			750lm	4000K	Black	TL21-12W-940-36-B	



Input Voltage / 输入电压 : 220-240V      Power Factor / 功率因数: 0.5  
 Weight / 重量 : 290g      Dimensions / 尺寸: Ø52x78x133mm



Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号	
25W	90	▲ 12°	1600lm	3000K	White	TL22-25W-930-12-W	
			1700lm	4000K	White	TL22-25W-940-12-W	
		▲ 24°	1600lm	3000K	White	TL22-25W-930-24-W	
			1700lm	4000K	White	TL22-25W-940-24-W	
		▲ 36°	1600lm	3000K	White	TL22-25W-930-36-W	
			1700lm	4000K	White	TL22-25W-940-36-W	
	1600lm		3000K	White	TL22-25W-930-36-W		
	1700lm		4000K	White	TL22-25W-940-36-W		
	25W	90	▲ 12°	1600lm	3000K	Black	TL22-25W-930-12-B
				1700lm	4000K	Black	TL22-25W-940-12-B
			▲ 24°	1600lm	3000K	Black	TL22-25W-930-24-B
				1700lm	4000K	Black	TL22-25W-940-24-B
▲ 36°			1600lm	3000K	Black	TL22-25W-930-36-B	
			1700lm	4000K	Black	TL22-25W-940-36-B	



Input Voltage / 输入电压 : 220-240V      Power Factor / 功率因数: 0.95  
 Weight / 重量 : 750g      Dimensions / 尺寸: Ø75x130x160mm

