



Tri-colour Series



IP54 Series

- Instant start, no flickering
  - Built-in high efficiency SMD LED chips
  - Constant current LED driver fitted
  - High performance PMMA diffuser
  - Optional motion sensor driver or emergency driver
  - High power factor >0.95
  - Long life, average 30,000 hours
- 立即启动，无闪烁
  - 高光效LED芯片，高流明输出
  - 内置恒流LED驱动
  - 亚克力灯罩，高透光，均匀无暗区
  - 可选配微波感应驱动，应急控制器
  - 功率因数>0.95
  - 长寿命30,000小时

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
22W	82	120°	1700lm	4000K	CD350-4000K
			1700lm	5700K	CD350-5700K



Input Voltage / 输入电压: 220-240V Power Factor / 功率因数: 0.95  
 Weight / 重量: 1400g Dimensions / 尺寸: Ø355x115mm

PMMA diffuser  
PMMA灯罩



CD350EM

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
22W	82	120°	1700lm	4000K	CD350EM-4000K
			1700lm	5700K	CD350EM-5700K



Input Voltage / 输入电压: 220-240V Power Factor / 功率因数: 0.95  
 Weight / 重量: 1400g Dimensions / 尺寸: Ø355x115mm

EM LED power 2.4W  
应急LED功率2.4W  
3 hours emergency  
应急时间3小时



C300

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号
13W	82	120°	900lm	3000K	White/Black/Silver/Chrome	C300-3000K
			950lm	4000K	White/Black/Silver/Chrome	C300-4000K



Input Voltage / 输入电压: 220-240V Power Factor / 功率因数: 0.95  
 Weight / 重量: 770g Dimensions / 尺寸: Ø300x70mm

Polycarbonate base and diffuser  
PC本体和PC灯罩



C350

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
22W	82	120°	1350lm	3000K	C350-3000K
			1400lm	4000K	C350-4000K



Input Voltage / 输入电压: 220-240V Power Factor / 功率因数: 0.95  
 Weight / 重量: 980g Dimensions / 尺寸: Ø350x90mm

Polycarbonate base and diffuser  
PC本体和PC灯罩

