

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
16W	82	120°	1100lm	3000K	CN275-3000K
			1200lm	4000K	CN275-4000K

Input Voltage / 输入电压: 220-240V

Power Factor / 功率因数: 0.95

Polycarbonate base and PMMA diffuser
PC本体和PMMA灯罩

Weight / 重量: 680g

Dimensions / 尺寸: Ø275x82mm



CN350

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
23W	82	120°	1500lm	3000K	CN350-3000K
			1600lm	4000K	CN350-4000K
			1600lm	5000K	CN350-5000K
			1600lm	5700K	CN350-5700K

Input Voltage / 输入电压: 220-240V

Power Factor / 功率因数: 0.95

Polycarbonate base and PMMA diffuser
PC本体和PMMA灯罩

Weight / 重量: 750g

Dimensions / 尺寸: Ø350x80mm



CN450

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
41W	82	120°	2700lm	3000K	CN450-3000K
			2800lm	4000K	CN450-4000K

Input Voltage / 输入电压: 220-240V

Power Factor / 功率因数: 0.95

Polycarbonate base and PMMA diffuser
PC本体和PMMA灯罩

Weight / 重量: 1320g

Dimensions / 尺寸: Ø450x103mm



CN275SN

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
16W	82	120°	1080lm/1200lm/1150lm	3000K/4200K/5700K	CN275SN

Input Voltage / 输入电压: 220-240V

Power Factor / 功率因数: 0.95

Polycarbonate base and PMMA diffuser
PC本体和PMMA灯罩

Weight / 重量: 610g

Dimensions / 尺寸: Ø275x83mm



CN350SN

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
20W	82	120°	1410lm/1600lm/1500lm	3000K/4200K/5700K	CN350SN

Input Voltage / 输入电压: 220-240V

Power Factor / 功率因数: 0.95

Polycarbonate base and PMMA diffuser
PC本体和PMMA灯罩

Weight / 重量: 910g

Dimensions / 尺寸: Ø350x89mm

