




Perfect Batten Light with Motion Sensor & Emergency Function

感应、应急全能支架灯




- Replacement for fluorescent lamps
- Surface mounted diffused batten
- Pressed steel casing and polycarbonate diffuser
- Built-in high efficiency SMD LED chips
- With constant current LED driver
- Suitable for use in emergency lighting systems
- High power factor >0.95
- Long life, average 30,000 hours



- 替代传统荧光灯支架使用
- 明装吸顶安装方式
- 金属支架粉末喷涂，高强度PC灯罩
- 高光效SMD LED芯片
- 恒流LED驱动
- 可匹配使用应急照明系统
- 功率因素>0.95
- 长寿命30,000小时

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
20W	82	120°	2000lm	4000K	BAS 2ft 20W 4000K
			2000lm	5700K	BAS 2ft 20W 5700K
20W	82	120°	2000lm	4000K	BAS 2ft 20W 4000K-EM ²
			2000lm	5700K	BAS 2ft 20W 5700K-EM ²


Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 1000g Dimensions / 尺寸: 615x84x70mm



BAS 4ft

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
40W	82	120°	4000lm	4000K	BA 4ft 40W 4000K
			4000lm	5700K	BA 4ft 40W 5700K
40W	82	120°	4000lm	4000K	BA 4ft 40W 4000K-MS ¹
			4000lm	5700K	BA 4ft 40W 5700K-MS ¹
40W	82	120°	4000lm	4000K	BA 4ft 40W 4000K-EM ²
			4000lm	5700K	BA 4ft 40W 5700K-EM ²
40W	82	120°	4000lm	4000K	BA 4ft 40W 4000K-MS-EM ^{1,2}
			4000lm	5700K	BA 4ft 40W 5700K-MS-EM ^{1,2}


Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 1950g Dimensions / 尺寸: 1221x84x70mm



BAS 5ft

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
60W	82	120°	6000lm	4000K	BAS 5ft 60W 4000K
			6000lm	5700K	BAS 5ft 60W 5700K

Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 2250g Dimensions / 尺寸: 1523x84x70mm



*1. Motion sensor / 微波感应 *2. Emergency / 应急