



- Super compact strip with SMD LED technology
- One bin per reel (in 3 step MacAdam)
- Anti-UV PU glue silicone coated
- Flexible Strip with 3M self-adhesive tapes at back for easy fixing
- Maximum angle of bend 120°
- Wide ambient temperature: -20°C~ +50°C
- Average life 50,000 hrs

- 超紧凑型贴片LED技术软灯条
- 单bin颜色控制，3SDCM标准，高一致性
- 抗老化耐黄变PU胶灌封
- 高强度3M背胶，便捷安装
- 120° 发光角度
- 使用环境温度：-20° C..+50° C
- 长寿命50,000小时

Power/Meter 功率/米	CRI 显色指数	Efficacy 光效	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
2.4W	82	115lm/W	250lm	4000K	F8-3528D0-12-30-IP20
			280lm	6000K	F8-3528F0-12-30-IP20

Package / 包装: 5m/Reel Dimensions / 尺寸: 5000x8x2mm



Power/Meter 功率/米	CRI 显色指数	Efficacy 光效	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
4.8W	82	105lm/W	450lm	2500K	F8-3528B5-12-60-IP20
			500lm	3200K	F8-3528C2-12-60-IP20
			500lm	4000K	F8-3528D0-12-60-IP20
			500lm	6500K	F8-3528F5-12-60-IP20
4.5W	82	105lm/W	450lm	2500K	F8-3528B5-12-60-IP65
			450lm	3200K	F8-3528C2-12-60-IP65
			500lm	6800K	F8-3528F8-12-60-IP65

Package / 包装: 5m/Reel Dimensions / 尺寸: 5000x8x3.5mm



Power/Meter 功率/米	CRI 显色指数	Efficacy 光效	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
9.6W	82	100lm/W	880lm	2500K	F8-3528B5-12-120-IP20
			900lm	3200K	F8-3528C2-12-120-IP20
			960lm	4000K	F8-3528D0-12-120-IP20
			960lm	6500K	F8-3528F5-12-120-IP20
9.6W	82	100lm/W	880lm	2500K	F8-3528B5-12-120-IP65
			900lm	3200K	F8-3528C2-12-120-IP65
			960lm	6500K	F8-3528F5-12-120-IP65

Package / 包装: 5m/Reel Dimensions / 尺寸: 5000x8x3.5mm



Power/Meter 功率/米	CRI 显色指数	Efficacy 光效	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
2.4W	82	100lm/W	240lm	6000K	F8-3528F0-24-30-IP20

Package / 包装: 30m/Reel Dimensions / 尺寸: 30000x8x2mm



Power/Meter 功率/米	CRI 显色指数	Efficacy 光效	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
23W	82	74lm/W	1700lm	3000K	F8-2835WW-24-96-IP20
		82lm/W	1900lm	4000K	F8-2835CW-24-96-IP20
		82lm/W	1900lm	5700K	F8-2835DL-24-96-IP20

Package / 包装: 5m/Reel Dimensions / 尺寸: 5000x8x2mm

