

- Super narrow rigid strip 5mm
 - single bin (in 3 step MacAdam)
 - 36 LEDs or 42 LEDs 500mm
 - 3M self-adhesive tapes at back for easy fixing
 - Beam angle 120°
 - Wide ambient temperature: -20°C..+50°C
 - Average life 50,000 hrs
- 超窄紧凑型硬灯条
 - 单bin颜色控制, 3SDCM标准, 高一致性
 - 长500mm, 36/42 pcs LED
 - 高强度3M背胶, 便捷安装
 - 120° 发光角度
 - 使用环境温度: -20° C..+50° C
 - 长寿命50,000小时



Power/Meter 功率/米	CRI 显色指数	Efficacy 光效	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
10W	82	80lm/W	750lm	3000K	R6-W2835-24-42-IP20
			800lm	6000K	R6-C2835-24-42-IP20



Dimensions / 尺寸: 520x9x5mm



Power/Meter 功率/米	CRI 显色指数	Efficacy 光效	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
10W	N/A	N/A	260lm	RGB	R7-RGB5050-24-36-IP20



Dimensions / 尺寸: 520x9x5mm

