

Application:

Installation in cobblestone paths, driveways, civil engineering, architecture, agriculture, light spaces building facades, swimming pools.

安装场所:

适合安装在鹅卵石路、小区道路、土木建筑、个性建筑风格、农业场所、建筑立面照明、游泳池等。



- Anodized aluminum housing, built-in LED strip
- Remote power supply and control unit
- Incl. 1m connection cable
- Seamless and shadowless alignment possible
- 24V DC linear luminaire
- IP67

- 阳极电镀铝本体，内置LED灯条
- 电源和控制器外置安装
- 配1米户外连接线
- 实现无阴影串接，光形均匀
- 24V直流输入灯具
- IP67



Power/Meter 功率/米	CRI 显色指数	Field Angles 光束角	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
4.8W	82	90°	160lm	3600K	LP3310-24-4.8W-830

160lm	3000K	LP3310-24-4.8W-RGBW
100lm	Green(520nm)	
30lm	Blue(470nm)	
50lm	Red(620nm)	



Weight / 重量: 1500g Dimensions / 尺寸: 1000x27x30mm



Power/Meter 功率/米	CRI 显色指数	Field Angles 光束角	Lumens/Meter 流明/米	CCT 色温	Model No. 型号
9.6W	82	90°	300lm	3600K	LP3320-24-9.6W-830

300lm	3000K	LP3320-24-9.6W-RGBW
200lm	Green(520nm)	
60lm	Blue(470nm)	
100lm	Red(620nm)	



Weight / 重量: 2550g Dimensions / 尺寸: 2000x27x30mm

