





LED High Bay

LED 工矿灯


- Forging aluminium heat sink
 - Powder coated finish
 - Polycarbonate diffuser
 - Efficiency: 110~130 lm /W
 - low power consumption
 - Instant on/off operation
 - Mercury free, lead free
 - Adjustable bracket for light positioning
 - Beam angle 110°
 - CRI>82
 - IP65 Rated
 - RoHS compliant
- 高纯度铝散热器，冷锻工艺
 - 防腐蚀粉末喷涂表面处理
 - 高强度PC扩散板/透镜
 - 高光效输出110~130lm/W
 - 节能超低功耗
 - 快速启动，无传统金卤灯闪烁
 - 无汞、无卤环保材料
 - 可调节角度安装支架
 - 出光角度110°
 - 高显色指数CRI>82
 - IP65
 - 符合欧盟RoHS指令




HBT Series




HBS Series



HBF Series




HBE Series



HBA Series

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
100W	82	110°	11500lm	4000K	HBT100-4000K
			11500lm	5000K	HBT100-5000K


Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 4000g Dimensions / 尺寸: Ø320x268mm



HBT150

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
150W	82	110°	17250lm	4000K	HBT150-4000K
			17250lm	5000K	HBT150-5000K


Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 4000g Dimensions / 尺寸: Ø320x268mm



HBT200

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
200W	82	110°	25200lm	4000K	HBT200-4000K
			25200lm	5000K	HBT200-5000K

Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 4800g Dimensions / 尺寸: Ø320x278mm



HBT300

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
300W	82	110°	37800lm	4000K	HBT300-4000K
			37800lm	5000K	HBT300-5000K

Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 6800g Dimensions / 尺寸: Ø320x289mm

