

Road Light

路灯

- Die-cast aluminum Housing(ADC12)
- Powder coated finish
- High efficiency SMD LED chips
- Optional lens for different kinds of road - lighting requirements
- Optional photo sensor
- Built-in constant current LED driver
- Stainless steel bolts
- Pluggable connector
- Long life, average 50,000 hours
- IP66
- IK08


- 压铸铝灯体
- 防腐蚀粉末喷涂表面处理
- 高效率LED芯片
- 多角度规格透镜, 适用不同道路灯光设计需求
- 可选光感应器
- 内置高可靠LED恒流驱动器
- 不锈钢螺丝紧固件
- 接插式连接器
- 寿命50,000小时
- IP66
- IK10

SLF180

Power 功率	CRI 显色指数	Distribution Types 光型	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号
180W	82	Type II	21600lm	4000K	Black/Grey	SLF180-840
			21600lm	5000K	Black/Grey	SLF180-850



Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 7.2kgs Dimensions / 尺寸: 579.5X360X105mm




SLF240

Power 功率	CRI 显色指数	Distribution Types 光型	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号
240W	82	Type II	28800lm	4000K	Black/Grey	SLF240-840
			28800lm	5000K	Black/Grey	SLF240-850



Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 8.3kgs Dimensions / 尺寸: 663x360x105mm



SLF300

Power 功率	CRI 显色指数	Distribution Types 光型	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号
300W	82	Type II	36000lm	4000K	Black/Grey	SLF300-840
			36000lm	5000K	Black/Grey	SLF300-850



Input Voltage / 输入电压 : 220-240V Power Factor / 功率因数: 0.95
 Weight / 重量 : 9.26kgs Dimensions / 尺寸: 746.5x360x105mm

