

# Ultrathin Ceiling Light

## 超薄吸顶灯



## Features / 产品特点

- Ultrathin design with even light spread
- Instant start, flicker-free
- Built-in high efficiency SMD LED chips
- Select colour temperature with DIP switch
- Constant current LED driver fitted
- High performance PMMA diffuser
- High power factor >0.95
- Long life, average 30,000 hours
- IP54 rated
- 超薄设计，出光均匀
- 立即启动，无频闪
- 高光效LED芯片，高流明输出
- 拨码调节色温
- 内置恒流LED驱动
- 亚克力灯罩，高透光，均匀无暗区
- 功率因数>0.95
- 长寿命30,000小时
- IP54防护等级


Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号
12W	82	115°	960lm/1060lm/1030lm	3000K/4200K/6000K	White	CT250TC-12W-WH
			960lm/1060lm/1030lm	3000K/4200K/6000K	Black	CT250TC-12W-BK



Input Voltage / 输入电压: 220-240V Power Factor / 功率因数: 0.95

Weight / 重量: 650g Dimensions / 尺寸: Ø250x40mm

PMMA diffuser  
PMMA灯罩



CT300


Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号
18W	82	115°	1450lm	3000K	White	CT300-18W-830-WH
			1550lm	4000K	White	CT300-18W-840-WH
			1450lm	3000K	Black	CT300-18W-830-BK
			1550lm	4000K	Black	CT300-18W-840-BK
			1450lm/1600lm/1550lm	3000K/4200K/6000K	White	CT300TC-18W-WH
			1450lm/1600lm/1550lm	3000K/4200K/6000K	Black	CT300TC-18W-BK
25W	82	115°	2000lm	3000K	White	CT300-25W-830-WH
			2150lm	4000K	White	CT300-25W-840-WH
			2000lm	3000K	Black	CT300-25W-830-BK
			2150lm	4000K	Black	CT300-25W-840-BK
			2000lm/2200lm/2150lm	3000K/4200K/6000K	White	CT300TC-25W-WH
			2000lm/2200lm/2150lm	3000K/4200K/6000K	Black	CT300TC-25W-BK



Input Voltage / 输入电压: 220-240V Power Factor / 功率因数: 0.95

Weight / 重量: 750g Dimensions / 尺寸: Ø300x38mm

PMMA diffuser  
PMMA灯罩



CT400

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Fitting Colour 颜色	Model No. 型号
30W	82	115°	2400lm/2600lm/2550lm	3000K/4200K/6000K	White	CT400TC-30W-WH
			2400lm/2600lm/2550lm	3000K/4200K/6000K	Black	CT400TC-30W-BK



Input Voltage / 输入电压: 220-240V Power Factor / 功率因数: 0.95

Weight / 重量: 990g Dimensions / 尺寸: Ø400x45mm

PMMA diffuser  
PMMA灯罩

