




## Batten Light

### 支架灯

- Replacement for fluorescent lamps
- Metal stamped housing with powder coated finish
- Reeded opal PC extrusion diffuser provides even light distribution
- Transparent end caps realizes a continuous line of light when aligned end-to-end
- Detachable LED engine for easy installation and replacement
- Built-in high efficiency SMD LED chips
- Emergency version available
- High power factor >0.95
- Long life, average 30,000 hours
- IP20 rated fixture, IP54 rated LED engine

- 替代传统荧光灯支架使用
- 金属支架粉末喷涂
- 高强度PC挤出条纹乳白灯罩，出光均匀柔和
- 灯罩端盖透明设计，串接安装无暗边
- 可拆装发光模组，方便安装和更换
- 高光效SMD LED芯片
- 可匹配使用应急照明系统
- 功率因素>0.95
- 长寿命30,000小时
- 整灯IP20, 光源模组IP54

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
20W	82	120°	2200lm	4000K	BAE 2ft 20W 4000K
			2200lm	5700K	BAE 2ft 20W 5700K




Input Voltage / 输入电压: 220-240V    Power Factor / 功率因数: 0.95  
 Weight / 重量: 800g    Dimensions / 尺寸: 612x71x74mm



BAE 4ft

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
40W	82	120°	4400lm	4000K	BAE 4ft 40W 4000K
			4400lm	5700K	BAE 4ft 40W 5700K




Input Voltage / 输入电压: 220-240V    Power Factor / 功率因数: 0.95  
 Weight / 重量: 1750g    Dimensions / 尺寸: 1218x71x74mm



BAE 5ft

Power 功率	CRI 显色指数	Beam Angles 光束角	Lumens 流明	CCT 色温	Model No. 型号
60W	82	120°	6600lm	4000K	BAE 5ft 60W 4000K
			6600lm	5700K	BAE 5ft 60W 5700K



Input Voltage / 输入电压: 220-240V    Power Factor / 功率因数: 0.95  
 Weight / 重量: 2050g    Dimensions / 尺寸: 1520x71x74mm

